

Product Data Sheet



Product description

Delo Silver are lubricating oils designed to lubricate a wide variety of equipment. It is suitable for use in applications for hydraulic, transmission and final drives and axles in older construction and mining equipment.

SAE 10W, SAE 30, 50:

Suitable for use in mobile hydraulic and transmission systems where this viscosity grade and performance level are appropriate

Customer benefits

- Prolongs periods between overhauls Proven metallo-organic anti-wear additive system resists wear by forming a protective layer on contact surfaces under all service conditions.
- Saves on maintenance Good oxidation stability resists oil degradation and protects against oil thickening, and oil line and filter plugging.
- Preserves power and performance Metallic detergent and ashless dispersant additive system preserves power and performance.

Applications

The following applications whenever the manufacturer recommends monograde lubricating oils:

- Transmission and final drives and axles of older off-highway equipment (where oil type and viscosity are appropriate)
- Off-highway vehicles
- Agricultural tractors
- Mobile hydraulic systems (where oil type and viscosity are appropriate)

Product highlights:

- Prolongs periods between overhauls
- Saves on maintenance
- Preserves power and performance
- High alkaline reserve



A Chevron company product







Key properties

DELO SILVER MONOGRADE	RESULTS		
SAE Grade	10W	30	50
Product Code	500585	500587	500589
Kinematic Viscosity,			
mm²/s @ 100°C	7.0	11.5	19.1
mm²/s @ 40°C	39	101	225
Viscosity Index	114	101	96
Base No., D2896, mg KOH/g	9.6	9.6	9.6
Zinc, m %	0.06	0.06	0.06
Calcium, m %	0.35	0.35	0.35

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by Chevron Lubricants; Africa, Middle East and Pakistan.

Environment, Health and Safety Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit www.caltexoils.com.

For more information, go to www.chevronlubricants.com